



AsReader (ASX-520R) Barcode Scanner



Name (Model Name)		ASX-520R (2D model)
Barcode	Scanning method	2D CMOS
	Minimum Resolution	0.102mm~0.508mm (4mil~20mil)
	Reading distance	50~760mm (1.97"~29.92") ※1
	Reading angle	Pitch:±60° Roll: 360° Skew motion:±60° ※1
	Readable code	<ul style="list-style-type: none"> ■ 1D: JAN/UPC/EAN, CODE11, CODE39, CODE93, CODE128, ITF(INTERLEAVED 2of5), DISCRETE 2of5, CHINESE 2of5, MATRIX 2of5, CODABAR(NW-7), MSI, GS1 DATABAR OMNIDIRECTIONAL, GS1DATABAR LIMITED, GS1DATABAR EXPENDED ■ 2D: PDF417, MicroPDF417, Datamatrix, QR Code, Micro QR Code, Aztec, RSS, Composite, TLC-39, MaxiCode Postal: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX)
	light sources	RED LED
Battery	Battery Capacity	Built-in rechargeable lithium-ion battery 700mAh
	Continuous operation time	36,000 times ※2
	Power Source	Magconn cable / DC Power cable ※3
	Charging time	About 2 hours (Built-in battery) ※4
Key input		2 trigger key
Communication	Interface	MFi on Lightning ※5
Appearance	Dimensions (W)x(D)x(H)	64.40 x 17.00 x 141.91mm *excluding protrusions
	Weight(with Battery)	Approx. 90g
	Material	PC (Polycarbonate) / TPU(Thermoplastic Polyurethane)
	Casing color	White/Gray
	LED	Non-blinking Blue LED ※6 : Connected with device.Blinking Blue LED: Reading RFID tag. Non-blinking Red LED: Battery is charging.Faint Red LED: Battery is fully charged
Environment	Operation environment	-10~45 °C、20~85 % RH (Charge 0 °C or more, however)
	Storage environment	-20~60 °C、10~95 % RH
	IP Rating	IP52 compliance
	Anti-drop	(Six-sided * 4 edge, once each) 1.5m ※7
Certificate		PSE / Apple MFi / FCC / CE / RoHS
Bundled items		Magconn cable/DC Power cable/Earphone extension cable/iPod touch sheet/Installation instructions manual/seal/Instruction Manual/Notice

- ※1 It may depend on a bar code type.
- ※2 36,000 times continuous reading on iPhone's default brightness setting.
- ※3 Standard iPhone 1A charger is strongly recommended to be used when using Magconn cable.
- ※4 iPhone and AsReader battery will be recharged simultaneously. iPhone and AsReader battery will be recharged in 3.5h and 2h respectively in simultaneous recharging mode.
- ※5 SDK is required and available for download, please contact us.
- ※6 Blue LED will turn on after iPhone/iPod is connected. LED will turn off after the first tag reading.
- ※7 iPhone screen may be broken depends on the drop angle
- Please confirm the latest information on our website.
- iPhone® and iPod touch® are registered trademarks of Apple® Inc. All other trademarks are property of their respective owners.

<http://www.asreader.com>